



DECLARATION OF PERFORMANCE

Nº DoP - 1010

Unique identification code of the product-type:

1010 (TOPCOLA CLÁSSICO)

Intended use/es

Tile adhesive for applying tiles on walls and floors inside, not suitable for use outdoors.

Manufacturer:

TOPECA, Lda,

Rua D. Nuno Álvares Pereira, 53, 2490-114 Cercal – Ourém, PORTUGAL

Tel.: 00 351 – 249 580 070 / Fax.: 00 351 – 249 580 079

www.topeca.com

Notified body/ies:

CTCV – Centro Tecnológico da cerâmica e do Vidro nº 855

Declared performance

| Harmonised standard: EN 12004:2007+A1:2012 | | Suntain (a) of AVCD |
|--|-------------|---------------------|
| Essential Characteristics | Performance | System (s) of AVCP |
| Reaction to fire | Class A1 | |
| Release of dangerous substances | See MSDS | |
| Bond strength, as: | | |
| Initial tensile adhesion strength | ≥ 0,5 N/mm² | 4 e 3 |
| Durability for: | | |
| Tensile adhesion strength after heat ageing | NPD | |
| Tensile adhesion strength after water immersion | ≥ 0,5 N/mm² | |
| Tensile adhesion strength after freeze-thaw cycles | NPD | |

MSDS – Material Safety Data Sheet - NPD – No Performance Determined; AVCP – Assessment and verification of constancy of performance;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ourém, November 16, 2016

Francisco Nunes (Technical Manager)

Francisco Numes





Do not copy Rev. 02