

# DECLARATION OF PERFORMANCE

Nº DoP – 1080

**Unique identification code of the product-type:**

1080 (TOPCOLA EPOXY)

**Intended use/es:**

Adhesive for tiles in the form of reaction resin adhesives (R1), for applying tiles on walls and floors inside, not suitable for use outdoors.

**Manufacturer:**

TOPECA, Lda,  
Rua D. Nuno Álvares Pereira, 53, 2490-114 Cercal – Ourém, PORTUGAL  
Tel.: 00 351 – 249 580 070 / Fax.: 00 351 – 249 580 079  
www.topeca.com

**Notified body/ies:**

CTCV – Technological centre of ceramics and glass nº 855.

**Declared performance:**

Harmonised standard: EN 12004:2007+A1:2012		System (s) of AVCP
Essential Characteristics	Performance	
Reaction to fire	Class F	4 and 3
Release of dangerous substances	See MSDS	
Initial shear adhesion strength	≥ 2 N/mm <sup>2</sup>	
Shear adhesion strength after thermal shock	≥ 0.5 N/mm <sup>2</sup>	
Shear adhesion strength after water immersion	≥ 2 N/mm <sup>2</sup>	

MSDS – Material Safety Data Sheet - AVCP – Assessment and verification of constancy of performance;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ourém, May 4, 2018



Francisco Nunes  
(Technical Manager)