# Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# 100699 - Arg Anti-humidade CF



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 100699 - Arg Anti-humidade CF

# 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Mortar. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Topeca, Lda

Rua Dom Nunes Alvares Pereira,nº 53

2490-114 Cercal - Ourém - Santarém - Portugal

Phone.: +351 249580070 -Fax: +351 249580079 geral@topeca.pt www.topeca.pt

1.4 Emergency telephone number: CIAV: +351 808 250 143

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) nº 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) no 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

#### 2.2 Label elements:

#### CLP Regulation (EC) no 1272/2008:

#### Danger





#### **Hazard statements:**

Eye Dam. 1: H318 - Causes serious eye damage Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

# **Precautionary statements:**

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310: Immediately call a poison center/doctor

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

# Substances that contribute to the classification

Cement, portland, chemicals; Flue dust, portland cement

#### 2.3 Other hazards:

Non-applicable

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:



# 100699 - Arg Anti-humidade CF



# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) no1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification			
CAS: 65997-15-1	Cement, portland, ch	emicals	Self-classified		
EC: 266-043-4 Index: Non-applicable REACH: Non-applicable	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 -	Danger 🗘 📀	50 - <75 %	
CAS: 68475-76-3	Flue dust, portland c	ement	Self-classified		
EC: 270-659-9 Index: Non-applicable REACH: 01-2119486767-17-XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	<b>(1)</b>	2,5 - <10 %	
CAS: 141-32-2	Butyl acrylate		ATP CLP00		
EC: 205-480-7 Index: 607-062-00-3 REACH: 01-2119453155-43-XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Stin	STOT SE (1)	<1 %	

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, containing flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

#### Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# 100699 - Arg Anti-humidade CF



# SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

#### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

# 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Use in ventilated areas. Avoid the build up of dust

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, manipulation and use.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5 Keep the container tightly sealed and protected from open air and humidity.

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



# 100699 - Arg Anti-humidade CF



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits			
Butyl acrylate	IOELV (8h)	2 ppm	11 mg/m <sup>3</sup>	
CAS: 141-32-2	IOELV (STEL)	10 ppm	53 mg/m <sup>3</sup>	
EC: 205-480-7	Year	2015		

# **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Flue dust, portland cement	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68475-76-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 270-659-9	Inhalation	Non-applicable	4 mg/m³	Non-applicable	1 mg/m³
Butyl acrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-32-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-480-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	11 mg/m <sup>3</sup>

# **DNEL (General population):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Flue dust, portland cement	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68475-76-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 270-659-9	Inhalation	Non-applicable	4 mg/m³	Non-applicable	1 mg/m³

#### PNEC:

Identification				
Flue dust, portland cement	STP	6 mg/L	Fresh water	0.028 mg/L
CAS: 68475-76-3	Soil	5 mg/kg	Marine water	0.003 mg/L
EC: 270-659-9	Intermittent	0.282 mg/L	Sediment (Fresh water)	0.875 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.088 mg/kg
Butyl acrylate	STP	3.5 mg/L	Fresh water	0.00272 mg/L
CAS: 141-32-2	Soil	1 mg/kg	Marine water	0.00027 mg/L
EC: 205-480-7	Intermittent	0.011 mg/L	Sediment (Fresh water)	0.0338 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.00338 mg/kg

# 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



# 100699 - Arg Anti-humidade CF



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against liquid splash	CATII	EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		
	Anti-slip work shoes	CATII	EN ISO 20347:2012	

# F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2002	<b>⊢</b>	DIN 12 899 ISO 3864-1:2002
Emergency shower		Eyewash stations	

# **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight

V.O.C. density at 20 °C:  $0.01 \text{ kg/m}^3 (0.01 \text{ g/L})$ 

Average carbon number: 7

Average molecular weight: 128.2 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Solid

Appearance: Not available
Color: Not available
Odor: Not available

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



# 100699 - Arg Anti-humidade CF



# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable \*

Non-applicable \*

Evaporation rate at 20 °C:

Non-applicable \*

**Product description:** 

Density at 20 °C: 2807 kg/m³ Relative density at 20 °C: 2.807

Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: Non-applicable \* Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \* Decomposition temperature: Non-applicable \* Melting point/freezing point: Non-applicable \* Explosive properties: Non-applicable \* Non-applicable \* Oxidising properties:

Flammability:

Flash Point: Non Flammable (>60 °C)

Autoignition temperature: 292 °C

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Avoid direct impact

# 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others



# 100699 - Arg Anti-humidade CF



# SECTION 10: STABILITY AND REACTIVITY (continued)

	Cilianta formation and calcium			
Incompatible	Silicate formation and calcium hydroxide	Avoid direct impact	Not applicable	Base metal salts (Al, NH4,)
	Hydroxide			

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A.- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Contact with human skin, without adequate protection, can result in skin thickening, cracking, or fissuring

Specific toxicology information on the substances:



# 100699 - Arg Anti-humidade CF



# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Ac	Acute toxicity	
Cement, portland, chemicals	LD50 oral	>2000 mg/kg	
CAS: 65997-15-1	LD50 dermal	>2000 mg/kg	
EC: 266-043-4	LC50 inhalation	>5 mg/L (4 h)	
Flue dust, portland cement	LD50 oral	>2000 mg/kg	
CAS: 68475-76-3	LD50 dermal	>2000 mg/kg	
EC: 270-659-9	LC50 inhalation	>5 mg/L (4 h)	
Butyl acrylate	LD50 oral	4000 mg/kg	
CAS: 141-32-2	LD50 dermal	>2000 mg/kg	
EC: 205-480-7	LC50 inhalation	>20 mg/L	

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Butyl acrylate	LC50	5.2 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 141-32-2	EC50	230 mg/L (24 h)	Daphnia magna	Crustacean
EC: 205-480-7	EC50	5.5 mg/L (96 h)	Selenastrum capricornutum	Algae

#### 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butyl acrylate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 141-32-2	COD	Non-applicable	Period	14 days
EC: 205-480-7	BOD5/COD	0.56	% Biodegradable	61.3 %

# 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Butyl acrylate	BCF	37	
CAS: 141-32-2	Pow Log	2.36	
EC: 205-480-7	Potential	Moderate	

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Butyl acrylate	Koc	Non-applicable	Henry	Non-applicable
CAS: 141-32-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 205-480-7	Surface tension	2.598E-2 N/m (25 °C)	Moist soil	Non-applicable

# 12.5 Results of PBT and vPvB assessment:

Non-applicable

# 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

# 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances	Dangerous	

# Type of waste (Regulation (EU) No 1357/2014):

HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising **Waste management (disposal and evaluation):** 

#### Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# 100699 - Arg Anti-humidade CF



# SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC)  $n^{o}1907/2006$  (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

Nο

#### **SECTION 14: TRANSPORT INFORMATION**

#### Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:

14.1 UN number: Non-applicable
 14.2 UN proper shipping name: Non-applicable
 14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
 14.4 Packing group: Non-applicable

14.5 Dangerous for the

environment:

14.6 Special precautions for user

Special regulations:

Tunnel restriction code:

Physico-Chemical properties:

Limited quantities:

Non-applicable

Non-applicable

Transport in bulk according

Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

#### Transport of dangerous goods by sea:

With regard to IMDG 37-14:

14.1 UN number: Non-applicable
 14.2 UN proper shipping name: Non-applicable
 14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
 14.4 Packing group: Non-applicable

**14.5 Dangerous for the** No

environment:

14.6 Special precautions for user

Special regulations: Non-applicable

EmS Codes:

Physico-Chemical properties: see section 9
Limited quantities: Non-applicable **Transport in bulk according** Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:

#### Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# 100699 - Arg Anti-humidade CF



# SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: Non-applicable
 14.2 UN proper shipping name: Non-applicable
 14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
 14.4 Packing group: Non-applicable

**14.5 Dangerous for the** No.

environment:

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **Transport in bulk according** Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

# **SECTION 15: REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Non-applicable

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

# Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# SECTION 16: OTHER INFORMATION

# Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EU) No 453/2010, Regulation (EC) No 2015/830)

# Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

# Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction

H335: May cause respiratory irritation

H315: Causes skin irritation

H318: Causes serious eye damage

# Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) no 1272/2008:

#### Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

# 100699 - Arg Anti-humidade CF



# SECTION 16: OTHER INFORMATION (continued)

Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

#### Classification procedure:

Skin Sens. 1: Calculation method STOT SE 3: Calculation method Skin Irrit. 2: Calculation method Eye Dam. 1: Calculation method

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://esis.jrc.ec.europa.eu http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol—water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.