

DECLARATION OF PERFORMANCE

Nº DoP –5070

Unique identification code of the product-type:

5070 (TOPCOLA THERM T2).

Intended use/es:

General purpose rendering mortar type (GP – CSIV – W_c1).

Intended use: in walls, ceilings, columns.

Manufacturer:

TOPECA, Lda,

Rua D. Nuno Alvares Pereira, 53, 2490-114 Cercal – Ourém, PORTUGAL

Tel.: 00 351 – 249 580 070 / Fax.: 00 351 – 249 580 079

www.topeca.com

Notified body/ies:

Not applicable.

Declared performance

Harmonised standard: EN 998-1:2016		System/s of AVCP
Essential Characteristics	Performance	
Reaction to fire	Class F	4
Water absorption	W _c 1	
Thermal conductivity (λ10,dry)	0.45W/m. K (tab. mean value, P=50%)	
Adhesion (concrete)	≥0.5 N/mm ² FP-B	
Water vapour permeability coefficient	μ≤20	
Durability	Evaluation valid in the intended place of use of the mortar	
Dangerous substances	See MSDS	

MSDS – Material Safety Data Sheet; AVCP – Assessment and Verification of Constancy of Performance.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) nº 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ourém, November 22th 2017



Francisco Nunes
(Technical Manager)