Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 155209 - Topeca Floor OUT Comp C - 5kg

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Speciality application. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Topeca, Lda

Rua Dom Nunes Alvares Pereira, nº 53

2490-114 Cercal - Ourém - Santarém - Portugal

Phone.: +351 249580070 -Fax: +351 249580079 geral@topeca.pt www.topeca.pt

1.4 Emergency telephone number: CIAV: +351 808 250 143

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) nº 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) no 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334

Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) nº 1272/2008:

Danger





Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

Precautionary statements:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P264: Wash thoroughly after use

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction

Substances that contribute to the classification

Hexamethylene diisocyanate, oligomers; 2-methoxy-1-methylethyl acetate; Xylene (mixture of isomers); Ethylbenzene

2.3 Other hazards:

Non-applicable



155209 - Topeca Floor OUT Comp C - 5kg



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Additive/s

Components:

In accordance with Annex II of Regulation (EC) nº1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS:	28182-81-2	Hexamethylene diiso	cyanate, oligomers	Self-classified	
	931-274-8 Non-applicable : 01-2119485796-17-XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	(!)	75 - <100 %
CAS:	108-65-6	2-methoxy-1-methyl	ethyl acetate	ATP ATP01	
	203-603-9 607-195-00-7 :01-2119475791-29-XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	(8)	10 - <25 %
CAS:		Xylene (mixture of is	omers)	ATP CLP00	
	215-535-7 601-022-00-9 :01-2119488216-32-XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	<u>(1)</u>	10 - <25 %
CAS:	100-41-4	Ethylbenzene		ATP ATP06	
	202-849-4 601-023-00-4 01-2119489370-35-XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	(!) (♣)	2,5 - <10 %
	822-06-0	Hexamethylene diiso	cyanate	ATP CLP00	
	212-485-8 615-011-00-1 1:01-2119457571-37-XXXX	Regulation 1272/2008	Acute Tox. 3: H331; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315 Sens. 1: H317; STOT SE 3: H335 - Danger	; Skin	<1 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, containing flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C



155209 - Topeca Floor OUT Comp C - 5kg



SECTION 7: HANDLING AND STORAGE (continued)

Maximum Temp.: 30 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	E	Environmental limits		
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³	
CAS: 108-65-6	IOELV (STEL)	100 ppm	550 mg/m ³	
EC: 203-603-9	Year	2015		
Xylene (mixture of isomers)	IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m ³	
EC: 215-535-7	Year	2015		
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m ³	
EC: 202-849-4	Year	2015		

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 28182-81-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 931-274-8	Inhalation	Non-applicable	1 mg/m³	Non-applicable	0.5 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	153.5 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	275 mg/m ³	Non-applicable
Xylene (mixture of isomers)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Hexamethylene diisocyanate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 822-06-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 212-485-8	Inhalation	0.07 mg/m ³	0.07 mg/m ³	0.035 mg/m ³	0.035 mg/m ³

DNEL (General population):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	1.67 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	54.8 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	Non-applicable
Xylene (mixture of isomers)	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14.8 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m³	Non-applicable

- CONTINUED ON NEXT PAGE -



Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

PNEC:

Identification				
Hexamethylene diisocyanate, oligomers	STP	38.3 mg/L	Fresh water	0.127 mg/L
CAS: 28182-81-2	Soil	53182 mg/kg	Marine water	0.0127 mg/L
EC: 931-274-8	Intermittent	1.27 mg/L	Sediment (Fresh water)	266700 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0.635 mg/L
CAS: 108-65-6	Soil	0.29 mg/kg	Marine water	0.0635 mg/L
EC: 203-603-9	Intermittent	6.35 mg/L	Sediment (Fresh water)	3.29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.329 mg/kg
Xylene (mixture of isomers)	STP	6.58 mg/L	Fresh water	0.327 mg/L
CAS: 1330-20-7	Soil	2.31 mg/kg	Marine water	0.327 mg/L
EC: 215-535-7	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12.46 mg/kg
Ethylbenzene	STP	9.6 mg/L	Fresh water	0.1 mg/L
CAS: 100-41-4	Soil	2.68 mg/kg	Marine water	0.01 mg/L
EC: 202-849-4	Intermittent	0.1 mg/L	Sediment (Fresh water)	13.7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1.37 mg/kg
Hexamethylene diisocyanate	STP	8.42 mg/L	Fresh water	0.0774 mg/L
CAS: 822-06-0	Soil	0.0026 mg/kg	Marine water	0.00774 mg/L
EC: 212-485-8	Intermittent	0.774 mg/L	Sediment (Fresh water)	0.01334 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.001344 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against liquid splash	CATII	EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection



155209 - Topeca Floor OUT Comp C - 5kg



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		
	Anti-slip work shoes	CATII	EN ISO 20347:2012	

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Emergency measure	Standards	Emergency measure	Standards
-3 *+	ANSI Z358-1 ISO 3864-1:2002	→	DIN 12 899 ISO 3864-1:2002
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 24.5 % weight

V.O.C. density at 20 °C: 261.68 kg/m³ (261.68 g/L)

Average carbon number: 7.02

Average molecular weight: 118.93 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Color:

Not available

Not available

Not available

Not available

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable *

Non-applicable *

Evaporation rate at 20 °C:

Non-applicable *

Product description:

Density at 20 °C: 1068 kg/m³ Relative density at 20 °C: 1.068

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

 * Not relevant due to the nature of the product, not providing information property of its hazards.



155209 - Topeca Floor OUT Comp C - 5kg



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration:

pH:

Non-applicable *

Vapour density at 20 °C:

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Autoignition temperature: 315 °C

Lower flammability limit:

Upper flammability limit:

Non-applicable *

Non-applicable *

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A.- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Ad	Acute toxicity	
Hexamethylene diisocyanate, oligomers	LD50 oral	5100 mg/kg	Rat
CAS: 28182-81-2	LD50 dermal	>2000 mg/kg	
EC: 931-274-8	LC50 inhalation	1.5 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Xylene (mixture of isomers)	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	1.5 mg/L (4 h) (ATEi)	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17.2 mg/L (4 h)	Rat
Hexamethylene diisocyanate	LD50 oral	>2000 mg/kg	
CAS: 822-06-0	LD50 dermal	>2000 mg/kg	
EC: 212-485-8	LC50 inhalation	0.5 mg/L (4 h) (ATEi)	Rat



155209 - Topeca Floor OUT Comp C - 5kg



SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Hexamethylene diisocyanate, oligomers	LC50	Non-applicable		
CAS: 28182-81-2	EC50	Non-applicable		
EC: 931-274-8	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Xylene (mixture of isomers)	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	0.6 mg/L (96 h)	Gammarus lacustris	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Hexamethylene diisocyanate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 822-06-0	COD	Non-applicable	Period	28 days
EC: 212-485-8	BOD5/COD	Non-applicable	% Biodegradable	28 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Xylene (mixture of isomers)	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low

12.4 Mobility in soil:

Identification	Absorpt	Absorption/desorption		Volatility	
Xylene (mixture of isomers)	Koc	202	Henry	5.249E+2 Pa·m³/mol	
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes	
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes	
Ethylbenzene	Koc	520	Henry	7.984E+2 Pa·m³/mol	
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes	
EC: 202-849-4	Surface tension	2.859E-2 N/m (25 °C)	Moist soil	Yes	

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described



Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) nº1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:

14.1 UN number: Non-applicable 14.2 UN proper shipping name: Non-applicable 14.3 Transport hazard class(es): Non-applicable Labels: Non-applicable 14.4 Packing group: Non-applicable 14.5 Dangerous for the

environment:

14.6 Special precautions for user

Special regulations: Non-applicable Tunnel restriction code: Non-applicable Physico-Chemical properties: see section 9 Limited quantities: Non-applicable Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 37-14:

14.1 UN number: Non-applicable 14.2 UN proper shipping name: Non-applicable 14.3 Transport hazard class(es): Non-applicable Lahels: Non-applicable 14.4 Packing group: Non-applicable

14.5 Dangerous for the

environment:

14.6 Special precautions for user

Special regulations: Non-applicable

EmS Codes:

Physico-Chemical properties: see section 9 Limited quantities: Non-applicable 14.7 Transport in bulk according

to Annex II of Marpol and the IBC Code:

Non-applicable

Transport of dangerous goods by air:

Safety data sheet According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IATA/ICAO 2015:

14.1 UN number: Non-applicable
 14.2 UN proper shipping name: Non-applicable
 14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
 14.4 Packing group: Non-applicable

14.5 Dangerous for the

environment:

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according** Non-applicable

to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Nο

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EU) No 453/2010, Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction H335: May cause respiratory irritation

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H315: Causes skin irritation H332: Harmful if inhaled

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) nº 1272/2008:

Safety data sheet

According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

155209 - Topeca Floor OUT Comp C - 5kg



SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H331 - Toxic if inhaled

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H335 - May cause respiratory irritation

Classification procedure:

Skin Sens. 1: Calculation method STOT SE 3: Calculation method Resp. Sens. 1: Calculation method Skin Irrit. 2: Calculation method Acute Tox. 4: Calculation method

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://esis.jrc.ec.europa.eu http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol—water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.