

PVC EXPANDED

Delivery program:

EXPANDED – AHTU; normal density, white

Dimensions:	Thickness:
2020×3050 mm	
1560×3050 mm	
1220×2440 mm	
1000×2000 mm	
1220×2440 mm	

2010×3050 mm	
1500×3050 mm	
1220×2440 mm	

EXPANDED – AYTU; ultralight density, white

Dimensions:	Thickness:
2020×3050 mm	
1560×3050 mm	
1220×2440 mm	
1000×2000 mm	

EXPANDED – AXTU; ultralight density, white

Dimensions:	Thickness:
2020×3050 mm	
1560×3050 mm	
1220×2440 mm	
1000×2000 mm	

1400×3050 mm	

EXPANDED–AHTN; coloured

Dimensions:	Thickness:
1560×3050 mm	

Standard colours:



Other colours are available on request.
Colours are indicative only.

Technical parameters:

Parameters	Unit	Types		
		AHTU/AHTN	AXTU	AYTU
Width	mm	1000-2020		
Tolerance on width	mm	1000-1559 +2,5; -1,0	1560-2020 +3,0; -1,0	
Length	mm	2000 - 3049		
Tolerance on length	mm	2000 - 3049 +5; -1	L ≥ 3050 +6; -1	
Thickness (S)	mm	1,2-6	8-19	2-6
Tolerance on thickness	mm	S±(0,1+0,05S)	S<15mm S±(0,1+0,05S) S>=15mm S±(0,1+0,03S)	S±(0,1+0,05S)
Deviation from the right angle	mm	max. 3mm/1000mm		

Typical applications of PVC EXPANDED:

- Advertising: signs, exhibition boards, displays, screen printing, digital printing, etc.
- Industry: fabrications, control cabinets and boards, etc.
- Construction: wall claddings, sandwich panels, interior decorations, etc.

Processing advices:

- Fabricating:** sawing, drilling, milling
- Thermal processing:** bending, thermoforming
- Others:** cren printing, digital printing, vinyl labeling, laminating, painting