

## TECHNICAL DATA SHEET

TOPECA, Lda Rua D. Nuno Alvares Pereira, 53 2490-114 Cercal – Ourém PORTUGAL

> Tel: 00 351 - 249 580 070 Fax: 00 351 - 249 580 079

> > geral@topeca.pt www.topeca.pt



### mortars for coatings

# topeca verniz gran

# varnishes for organic coatings



### Use

Finishing type varnish for organic coating type Rebetop Gran, promotes a shiny appearance to the surface.



- great flexibility
- glossy finish
- UV resistant

## surfaces

#### **Outside/Inside:**

• Supports coated finish system type Rebetop Gran





Pág. 2

# topeca verniz gran

varnishes for organic coatings

### recommendations

Do not apply to horizontal surfaces or surfaces angled at less than 45°. Do not apply to wet surfaces.

Protect upper edges of coating from rain water penetration by using protective strips. Do not apply to:

- -Frozen surfaces or when a risk of frost exists in next 48 hours;
- -Very hot surfaces;
- -When weather is excessively hot;

-When raining or under conditions of high atmospheric humidity.

Tools should be cleaned with water before product dries.

The Topeca Verniz Gran must be applied to the organic coating after complete drying thereof.

### mortars for coatings

# composition and characteristics

#### Composition:

Resins dispersed in water, colored sand and special additives.

### **Characteristics:**

Application temperature: 5°C to 30°C. Waiting time before carrying out finish: 15-30 minutes.

Note: Times given were calculated under normal conditions (Temperature  $20^{\circ}\text{C}\text{)}$ 

### colour

White. After drying, colorless

### consumption

It varies depending on the particle size of the organic coating. As given guidance: 200g/m<sup>2</sup>.

## available in

Buckets of 5 kg.

### storage

1 year from date of manufacture in a sealed packet stored in a damp free environment.



# topeca verniz gran

varnishes for organic coatings

application

## preparation of surface

Homogenize the product before application.

Substrates must be clean, flat, dry, free of oils and fats. Check the degree of adhesion and strength of the organic coating. The organic coating should be completely dry (approximately 7 days) prior to application of Topeca Verniz Gran.

Spread the product over the entire surface with a roller or brush for fine, filling the empty

space with varnish.



### mortars for coatings





