special products

toplimpa bic

product active and safe cleaning for user



use

Toplimpa Bio is a cleaner specifically designed for cleaning concrete and cement residue on: vehicles, concrete mixers, tools, walls lined with ceramic brick facings, natural stone, exposed surfaces in pre-industrial concrete mix.

Product indicated for the first cleaning of the work (bathrooms, kitchens), in order to remove residual cement.

Biodegradable product and easy to apply..

The Toplimpa Bio becomes active in the presence of cementitious waste, without the release of its activity immediately as with other products made from strong acids.

It contains no organic solvents or heavy metals and is phosphate free.

surface

- Mixers;
- Tools;
- · Concrete pumps;
- · Brick walls;
- Floors and walls







toplimpa bio

product active and safe cleaning for user

special products

recommendations

Do not mix with other products.

It is advised to practice pretests.

Apply Toplimpa Bio in well ventilated areas.

Toplimpa Bio not attack most plastics and paints of good quality, having little effect on steel, stainless steel, copper, brass and bronze and only a slight effect on aluminum, being more aggressive on zinc surfaces.

composition and characteristics

Composition:

Salts of organic solution and specific additives.

Characteristics:

Density: 1120 kg/m³

pH: 1,0.

colour

Yellow

consumption

Depending on conditions of work surfaces and dirt. How guidance given = 100 to 400ml / m^2 .

available in

Container 1 and 5 liters.

storage

12 months in closed under ice, heat, light and away from heat sources package.





toplimpa bio

product active and safe cleaning for user

special products

preparation of surface

Protect all areas that may be damaged during the application of Toplimpa Bio. Apply preferably on dry substrates.



application

The Toplimpa Bio can be used pure (for specific applications) or diluted in water in a ratio of 1 Toplimpa Bio: 4 water. Apply manually with brush over the surface.

Clean with water jet in order to clear the bracket before the surface dries.

In case of very stubborn stains, repeat the operation.



