



Enjoy Comfort Anywhere With Floorpan!





## THE ADVANTAGES OF FLOORPAN LAMINATE FLOORING




 FAST AND EASY ASSEMBLY


 SUITABLE FOR UNDERFLOOR HEATING


 RESISTANT TO UV RAYS


 RESISTANT TO POINT STRIKES


 ENVIRONMENTALLY FRIENDLY

 **HDF** BASE PANEL, HIGH DENSITY FIBERBOARD


 RESISTANT TO CIGARETTE FIRE

 RESISTANT TO SCRATCH

 EASILY CLEANED AND MAINTAINED, HYGIENIC

 NOT AFFECTED BY STAINS

 RESISTANT TO FURNITURE WHEEL ABRASION

 **E1** E1 GRADE

### LAMINATE FLOORING CLASSIFICATION

CLASS	21	22	23	31	32	33	34
UTILIZATION	AC1	AC2	AC3		AC4	AC5	AC6
ABRASION RESISTANCE	≥ 500	≥ 1000	≥ 2000		≥ 4000	≥ 6000	≥ 8500
RESISTANCE TO STAINS	Min. 4 (group 1 and 2) Min. 3 (group 3)		Min. 5 (group 1 and 2) Min. 4 (group 3)			Min. 5 (group 1, 2 and 3)	




PRODUCT	PANEL SIZE	THICKNESS	SURFACE	PANEL / PACKAGE	PACKAGE m <sup>2</sup>	PACKAGE / PALLET	PACKAGE kg
FLOORPAN CLASSIC	8x197x1205 mm	8 mm	Timberland	8 Pieces	1,89m <sup>2</sup>	60 Pieces	~14 kg









SE: SELECT / KASTAMONU EX: EXCLUSIVE / GEBZE PL: PLUS / ADANA

### TECHNICAL DATA SHEET

## FLOORPAN CLASSIC

8 MM - CLASS 32 - AC4

THICKNESS	mm	8	EN 13329+A1	
WIDTH	mm	197	EN 13329+A1	
LENGHT	mm	1205	EN 13329+A1	
SURFACE	Timberland			
EUROPEAN STANDARD	-	  	EN13329	
<b>PACKAGE THE DETAILS</b>				
PIECE	8 piece / 1 package			
M <sup>2</sup>	1,899 m <sup>2</sup>			
KG	14 kg			
<b>PALLET THE DETAILS</b>				
PIECE	60 package / 1 pallet			
M <sup>2</sup>	113,94 m <sup>2</sup>			
KG	840 kg			
CLASS	-	32	EN 13329+A1	
ABRASION RESISTANCE	-	AC4	EN 13329+A1	
THICKNESS SWELLING	%	≤18	ISO 24336	
RESISTANCE TO IMPACT	SMALL BALL	N	≥12	EN 13329+A1
	LARGE BALL	mm	≥750	EN 13329+A1
WARRANTY DOMESTIC / COMMERCIAL	Years	15/10	-	
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438	
SURCAFE SOUNDNESS	N/mm <sup>2</sup>	≥1.25	EN 13329+A1	
LOCK STRENGTH	LENGHT	kN/m	f10,2 ≥ 1	ISO 24334
	WIDTH	kN/m	fs0,2 ≥2	
EFFECT OF CASTOR CHAIR <sup>a</sup>	25.000 Cycles	No Damage <sup>a</sup>		EN 425:2002 <sup>b</sup>
EFFECT OF A FURNITURE LEG	-	No damage shall be visible when tested with foot type 0		EN 424
OPENING BETWEEN ELEMENTS. (0)	mm	0 average ≤ 0,15 mm 0 max. ≤ 0,20 mm		EN 13329+A1
HEIGHT DIFFERENCE BETWEEN ELEMENTS, (H)	mm	h average ≤ 0,10 mm h max. ≤ 0,15 mm		EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322	
FIRE RESISTANCE	Class	C <sub>s</sub> S1	EN 9239-1	
FORMALDEHYDE EMISSION	mg/m <sup>2</sup> h	≤3,5 (E1)	EN 12460-3	

Our products can also be produced with FSC and CARB certification upon request.