

# Aluminium Foil

# **SEALING-TAPE**

## TECHNICAL SPECIFICATIONS

### GENERAL SPECIFICATIONS

Item number	3034917
Product	noma®floor Aluminium foil sealing tape
Material	Aluminium Foil
Delivery form	Roll
Packing	50 m

### MATERIAL SPECIFICATIONS

<i>Parameter</i>	<i>Specification</i>	<i>Tolerance</i>	<i>Test method</i>
Thickness [mm]	0.05	± 10%	EN 823
Length [m]	50	± 1%, min. ± 3mm	EN 822
Width [m]	0.05	± 2mm	EN 822
Fire protection classification (RTF)	E <sub>fl</sub>	n. a.	
Thermal conductivity group	< 0,005m <sup>2</sup> K/W	n. a.	DIN 4108
Water absorption [%]	≤ 1%	n. a.	

**noma®floor**  
THE PERFORMANCE UNDERLAY

Remark: All above values are determined at laboratory conditions and with defined laboratory test sets. They can deflect in praxis or with other system components. For all performance data tolerances are possible due to uncertainty of the test method.

The above statements reflect the current state of our knowledge, providing information about our products and their application. Therefore they can not guarantee particular product features or suitability for a specific application. Subject to modification, legal liability can not be derived from this information.

Existing commercial patents must be observed.

May 18, all previous technical specifications are invalid



**NMC S.A.**

Gert-Noël-Strasse · B-4731 Eynatten T: +32 87 85 85 00 M: info@nmc.eu  
MwSt./TVA/BTW/VAT: BE- 0402 469 826 · RJP/RPM/RPR Eupen